



## RUBBASEAL™ SILICONE SEALANTS

### RUBBASEAL™ SILICONE SEALANT FOR HI- AND LO-TEMP FOODSERVICE USES

- Premium grade, fully certified silicone adhesive sealant outperforms cheap hardware store brands.
- Waterproof adhesive bonds better than generic sealants; won't peel, reduces service call-backs for leaks.
- Air-cures overnight; tack-free in 15 min.
- Standard and high temperature formulas.
- Meets Federal and NSF standards for foodservice use.

#### EASY TO USE

- RubbaSeal™ adhesive sealant won't sag during application. Apply vertically, horizontally or overhead.
- One-piece, rigid plastic cylinder fits all standard caulking guns.
- Nozzle is removable for easy cleaning and reuse after tube is opened.

#### SPECIFICATIONS

**TEMPERATURE RANGES:** Standard formula is serviceable from -80° F to 450° F. (-62° to 232° C). High temperature formula is heat resistant to 600° F. (316° C).

**PACKAGING:** Two sizes available; see Ordering Information.

#### SILICONE SEALANT

Model No.	Tube Size	Color	Max. Temp. (Degrees F.)	Quantity/ Carton	Approximate Weight/ Carton
3700000001	10.3 oz. (304ml)	Clear	450	12	10.4 lb. (4.7kg)
3700000002	10.3 oz. (304ml)	White	450	12	10.4 lb. (4.7kg)
3700000003	10.3 oz. (304ml)	Aluminum	450	12	10.4 lb. (4.7kg)
3700000004	10.3 oz. (304ml)	Black	450	12	10.4 lb. (4.7kg)
3700000005	10.3 oz. (304ml)	Red (HiTemp)	600	12	10.4 lb. (4.7kg)
3700000032	3 oz. (88.7ml)	White	450	36	9.1 lb. (1.4kg)
3700000033	3 oz. (88.7ml)	Aluminum	450	36	9.1 lb. (1.4kg)

Clear, Black and Hi-Temp Red are available in 3 oz. (88.7ml) tubes on special order. Contact your Kason representative.

NSF listed STD 051 for Food Zone Use. All Foods. Authorized by USDA for use in Federally inspected meat and poultry plants. When cured and washed, sealant meets requirement of FDA regulation No. 21 CFR177.2600. Meets the following: U.S. FED.TTS-00230C, TTS-001543A, ASTM C920-79, MIL-A-46106 and Canadian CGSB-19-GP-9MA Type 1. UL Recognized, File No. E175317.